



TECHNICAL SPECIFICATIONS

System

Frequency response (1)	38 Hz - 20 kHz
Recommended amplifier power	50 to 400 W rms into 8 Ω
Power handling(2)	Average (2) Programme 200 W rms 400 W rms
Nominal Impedance	8 Ω
Sensitivity (3)	98 dB SPL / 1 W @ 1 m
Distortion	< 0.5 %
Dispersion (@ -6dB)	90° conical
Crossover frequency	1100 Hz
Crossover controls	Treble energy range 2kHz – 25kHz +1.5dB, Level, -1.5dB
Drive unit	15" Tannoy Dual Concentric type 3833GG
Low frequency design	Optimised bass-reflex load, in 100 litres
Cabinet construction	MDF (36 mm front and rear panel) with energy absorbing bracing matrix.
Cabinet finish	Velti shadow grey soft-texture finish. High-pressure twin laminate in shadow grey with metallic speckled finish on top, bottom and sides.
Cabinet dimensions (HxWxD)	840 mm x 550 mm x 440 mm
Cabinet weight	45 kg
Shipping dimensions (HxWxD)	940 mm x 650 mm x 540 mm
Shipping weight	50 kg

NOTES : (1) +/- 3 dB , measured at 1m in an anechoic chamber.
(2) Long term power handling capacity as defined in EIA standard RS426A.
(3) Averaged over specified bandwidth for half-space environment. For anechoic conditions the figure is to be decreased by 3 dB.